

**THANK YOU FOR TRUSTING US!**

Products	Visible Light Transmittance	Total Solar Transmittance	Total Solar Reflectance	Total Solar Absorbance	Visible Light Reflectance Interior	Visible Light Reflectance Exterior	Winter U-Value	UV Rejected	Glare Reduction	Shading Coefficient	Solar Heat Gain Coefficient	IR Rejected @980nm	Total Solar Energy Rejected
Exterior 70% SolarGlaze™ 2 ply	67%	50%	14%	36%	9%	8%	1.02	99%	24%	0.63			45%
Exterior 20% Titanium- INF 2 ply	24%	22%	29%	49%	31%	31%	1.1	99%	73%	0.41			61%
Exterior 35% Titanium- INF 2 ply	44%	39%	17%	44%	18%	18%	1.1	99%	50%	0.59			49%
Exterior 20% Silver HP 2 ply	16%	13%	62%	25%	58%	60%	0.99	99%	82%	0.22			80%
Exterior 35% Silver HP 2 ply	26%	22%	50%	28%	47%	47%	0.99	99%	70%	0.33			71%
Exterior 50% Silver HP 2 ply	47%	37%	33%	33%	31%	31%	1.03	99%	47%	0.52			55%

Note: All data values above are representative and are provided for comparison purposes only.